

Fortus 380mc and 450mc

Get the latest FDM® technology for advanced prototyping and production.

Bring the speed, agility and design freedom of advanced additive manufacturing to your business while gaining the latest advances in FDM technology. The Fortus 380mc[™] and Fortus 450mc[™] 3D Production Systems build high-requirement prototypes, rugged jigs, fixtures and tooling, and custom production parts in familiar thermoplastics. And these 3D production systems are engineered for ease of use, including an all-new, intuitive touchscreen interface for smooth workflow. Both let you choose materials individually or in economical bundles.

Fortus 380mc:

Quickly build advanced prototypes and production aids as large as 355 x 305 x 305 mm (14 x 12 x 12 in.) in eight standard and engineering thermoplastics.

Fortus 450mc:

Get all the capabilities of the Fortus 380mc, plus a larger build envelope (406 x 355 x 406 mm [16 x 14 x 16 in.]) and the option to run high-performance thermoplastics for specialized production parts in demanding fields such as medical, aerospace, research and defense.









Fortus 380mc and 450mc



At the core: Advanced FDM technology

Fortus® systems are based on Stratasys® FDM technology. FDM builds parts in production-grade thermoplastics, enabling the most durable parts.

Fortus systems use a wide range of thermoplastics with advanced mechanical properties so your parts can endure high heat, caustic chemicals, sterilization and high-impact applications.

No special facilities needed

You can install a Fortus 3D Production System just about anywhere. No special venting is required because Fortus systems produce no noxious fumes, chemicals or waste.

No special skills needed

Compared to other additive fabrication systems, Fortus 3D Production Systems are easy to operate and maintain as there are no messy powders to handle and contain. They're so simple, an operator can be trained to operate a Fortus system in less than 30 minutes.

Get your benchmark on the future of manufacturing

Fine details. Smooth surface finishes.

Accuracy. Strength. The best way to see the advantages of a Fortus 3D

Production System is to have your own part built on a Fortus system.

Get your free part at: stratasys.com

\sim		\sim	 	•
	/stem		1001	1000
	/51611		11.01	10115
	OCULL	\sim	I U U L	

SYSTEM CONFIGURATION

Build Envelope (XYZ) 380mc: 355 x 305 x 305 mm (14 x 12 x 12 in.) 450mc: 406 x 355 x 406 mm (16 x 14 x 16 in.)

Material Delivery 380mc: One bay each for material and support canisters 450mc: Two bays each for material and support canisters

Material Delivery 380mc: One bay each for material and support canisters 450mc: Two bays each for material and support canisters

Auto changeover between canisters

Material Options									
	0.330 mm (0.013 in.)	LAYER 1 0.254 mm (0.010 in.)	THICKNESS 0.178 mm (0.007 in.)	0.127 mm (0.005 in.)	SUPPORT STRUCTURE	AVAILABLE COLORS			
ABS-ESD7™		Х	Х		Soluble	■ Black			
ABS-M30™	Х	х		X	Soluble	□ Ivory □ White ■ Black ■ Red ■ Blue ■ Dark Gray			
ABS-M30i™	Х	Х	Х	Х	Soluble	☐ Ivory			
ASA	X	x	X	х	Soluble	■ Black ■ Dark Blue ■ Dark Gray ■ Green ■ Light Gray Yellow □ White ■ Orange □ Ivory ■ Red			
FDM Nylon 12™	Х	Х	Х		Soluble	■ Black			
PC	×	х	X	Х	Breakaway, Soluble	White			
PC-ABS	Х	х	Х	Х	Soluble	■ Black			
PC-ISO™	х	Х	Х		Breakaway	☐ Translucent Natural ☐ White			
ULTEM® 9085 resin (450mc only)	Х	X			Breakaway	■ Tan ■ Black			
ULTEM 1010 resin (450mc only)	х	Х			Breakaway	Natural			
ST-130 (450mc only)		Only available in 0.330 mm (0.013 in.)			Breakaway	Tan			

OTHER SPECIFICATIONS						
System Size and Weight	129.5 cm x 90.2 cm x 198.4 cm (51 x 35.5 x 78.1 in.) 601 kg (1325 lbs.)					
Achievable Accuracy	Parts are produced within an accuracy of ± .127 mm (± .005 in.) or ± .0015 mm/mm (± .0015 in/in), whichever is greater). Z part accuracy includes an additional tolerance of -0.000/+slice height. Note: Accuracy is geometry dependent. Achievable accuracy specification derived from statistical data at 95% dimensional yield.					
Network Communication	10/100 base T connection. Ethernet protocol.					
Operator Attendance	Limited attendance for job start and stop required.					
Power Requirements	208VAC 3 phase, 50/60 Hz, consumes 18 Amps					
Regulatory Compliance	CE					
Software	All Fortus systems include Insight™ and Control Center™ job processing and management software. Compatible with GrabCAD Print for use with job reports, scheduling and remote monitoring.					
Operating System	Microsoft Windows 8.1 and Windows 8 (Pro, Enterprise), Microsoft Windows 7 (Pro, Enterprise, Ultimate), Microsoft Windows Vista (Business, Enterprise, Ultimate), Microsoft Windows Server 2008, Microsoft Windows Server 2003					





3-4 Innovation Way North Staffs Business Park Stoke on Trent ST6 4BF