



VeroFlex

POLYJET MATERIAL FOR EYEWEAR PROTOTYPING

VeroFlex™ is a PolyJet™ rigid photopolymer material offering a flexibility ideal for rapid prototyping eyewear. Get prototypes with full-part realism in a wide range of colors, textures and materials from opaque to transparent, unique to the Stratasys J735™ and Stratasys J750™ 3D Printers.

VeroFlex accurately simulates the look, feel and function of eyewear, enabling improved performance testing. Eyewear prototypes produced with Veroflex can better withstand drop tests, lens-mounting and wearability tests.

Shorten product development cycles down to one to two months with a more efficient design workflow. Respond to market trends faster and improve eyewear sales with VeroFlex on your Stratasys J735 or J750 3D Printer.



TO LEARN MORE ABOUT VEROFLEX VISIT [STRATASYS.COM](https://www.stratasys.com)



TRI-TECH 3D
STANFORD MARSH GROUP

THE 3D PRINTING SOLUTIONS COMPANY™



VeroFlex

POLYJET MATERIAL FOR EYEWEAR PROTOTYPING

At the core:

PolyJet Technology

PolyJet technology creates precise prototypes that set the standard for finished-product realism. Their fine resolution makes complex shapes, intricate details and smooth surfaces possible. PolyJet 3D Printing works by jetting layers of liquid photopolymer onto a build tray and instantly curing them with UV light. The fine layers build up to create a precise 3D model or prototype. Models are ready to handle right out of the 3D printer, with no post curing needed.

Keep valuable resources in-house

You'll be amazed when you see how easy it is to produce realistic models in-house. PolyJet 3D Printers offer not only unparalleled speed, they make it easy for you to print with the widest range of material properties.

No special facilities needed

You can install PolyJet 3D Printers just about anywhere. No special venting is required because PolyJet 3D Printers don't produce noxious fumes, chemicals or waste.

Good ideas sell easier

PolyJet 3D Printers improve communication and collaboration because they produce amazingly accurate representations of your ideas that you can share with your team and your clients for a faster, more confident buy-in.

MECHANICAL PROPERTIES	TEST METHOD	VALUE
Tensile Strength	D-6338-03	43 – 64 MPa (6,237 – 9,282 psi)
Elongation at Break	D-638-05	8 – 20% (8 – 20%)
Modulus of Elasticity	D-638-04	950 – 1,600 MPa (137,786 – 232,060 psi)
Flexural Strength	D-790-03	48 – 88 MPa (6,962 – 12,763 psi)
Flexural Modulus	D-790-04	1,600 – 2,300 MPa (232,061 – 333,587 psi)

OTHER	TEST METHOD	VALUE
Shore Hardness	D-2240	75-85 Scale D
HDT, @ 0.45 MPa	D-648-06	42 – 50 °C (108 – 122 °F)
Izod Notched Impact	D-256-06	20 – 30 J/m (0.375 – 0.562 lb/in)

SYSTEM AVAILABILITY	SOFTWARE	SUPPORT STRUCTURE	LAYER THICKNESS CAPABILITY	AVAILABLE COLORS
Stratasys J735/J750	GrabCad Print™ 1.8 Advance Material upgrade required	SUP705 (WaterJet removable)	High Quality mode: 14 microns (0.00055 in.) High Mix mode: 27 microns (0.001 in.)	VeroFlex Cyan™ VeroFlex Magenta™ VeroFlex Yellow™ VeroFlex White™ VeroFlex Black™ VeroFlex Clear™



STRATASYS.COM
ISO 9001:2008 Certified

©2017, 2018 Stratasys Ltd. All rights reserved. Stratasys, Stratasys signet, Stratasys J735, Stratasys J750, VeroFlex, Objet Studio, GrabCAD Print, SUP706, VeroFlex Cyan, VeroFlex Magenta, VeroFlex Yellow, VeroFlex White, VeroFlex Black, VeroFlex Clear and PolyJet are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries or affiliates and may be registered in certain jurisdictions. All other trademarks belong to their respective owners. Product specifications subject to change without notice. Printed in the USA. MSS_PJ_VeroFlex_0418a



Headquarters:
3-4 Innovation Way
North Staffs Business Park
Stoke-On-Trent
ST6 4BF
www.tritech3d.co.uk | info@tritech3d.co.uk