



Objet260 Connex3

**Multi-color, multi-material or versatility?
Choose all three for your office.**

Unleash your creativity with the most advanced office 3D printer: The Objet260 Connex3™. The Connex3 empowers you to 3D print brilliantly colored prototypes to fit your application needs. The Objet260 Connex3 boasts the widest range of material properties for its class, from rigid to flexible, transparent to opaque, neutral to vibrant, standard to bio-compatible and durable to high temperature. With Connex3, incorporate dozens of colors into one prototype, from vivid opaque to stained glass-like translucent, with hundreds of blended hues in between. GrabCAD Print™ software makes it simple to build high-quality, accurate 3D models.



LEARN MORE ABOUT THE OBJET260 CONNEX3 AT STRATASYS.COM



TRI-TECH 3D
STANFORD MARSH GROUP

THE 3D PRINTING SOLUTIONS COMPANY™



Objet260 Connex3

Driven by powerful PolyJet™ technology

Proven PolyJet 3D Printing is famous for smooth surfaces, fine precision and diverse material properties. It works a bit like inkjet document printing, but instead of jetting drops of ink onto paper, the print head jets microscopic layers of liquid photopolymer onto a build tray and instantly cures them with UV light. The fine layers build up to create a prototype or production part.

Along with the selected model material, the 3D printer features two support material options: SUP705, removed with a WaterJet; and SUP706, which is easily removed and soluble for automated post-processing and increased geometric freedom to print complex and delicate features and small cavities.

With its astonishingly realistic aesthetics and ability to deliver special properties such as transparency, flexibility and even bio-compatibility, PolyJet 3D Printing offers a competitive edge in consumer products prototyping, precision tooling and specialized production parts.

3D Printer Specifications

Model Materials	Rigid Opaque: VeroPureWhite™, VeroWhitePlus™, VeroBlackPlus™, VeroGray™, VeroBlue™, VeroCyan™, VeroMagenta™, VeroYellow™, VeroMagentaV™, VeroYellowV™ Rubber-like: Agilus30™, TangoPlus™, TangoBlackPlus™, TangoBlack™, TangoGray™ Transparent: VeroClear™ and RGD720 Simulated Polypropylene: Rigur™ and Durus™ High Temperature Bio-compatible
Digital Materials	Vibrant blended colors in Rigid Opaque Translucent colored tints Rubber-like materials in a variety of Shore A values Digital ABS Plus™ for durability, including blends with rubber Simulated polypropylene materials with improved heat resistance
Material Options	Over 1,000
Maximum Materials per Part	82
Support Material	SUP705 (WaterJet removable) SUP706 (soluble)
Maximum Build Size (XYZ)	255 x 252 x 200 mm (10.0 x 9.9 x 7.9 in.)
System Size and Weight	87 x 120 x 73.5 cm (34.2 x 47.2 x 29 in.); 264 kg (581 lbs.) Material Cabinet: 33 x 117 x 64 cm (13 x 46.1 x 25.2 in.); 76 kg (168 lbs.)
Resolution	X-axis: 600 dpi; Y-axis: 600 dpi; Z-axis: 1600 dpi
Accuracy	Up to 200 microns for full model size (for rigid materials only, depending on geometry, build parameters and model orientation)
Minimum Layer Thickness	Horizontal build layers as fine as 16 microns (.0006 in.)
Build Modes	Digital Material: 30-micron (.001 in.) resolution High Quality: 16-micron (.0006 in.) resolution High Speed: 30-micron (.001 in.) resolution
Software	Objet Studio™ intuitive 3D printing software. Compatible with GrabCAD Print for use with job reports, scheduling and reports monitoring.
Workstation Compatibility	Windows 7 or Windows 8
Network Connectivity	LAN - TCP/IP
Operating Conditions	Temperature 18-25°C (64-77°F); relative humidity 30-70% (non-condensing)
Power Requirements	110-240 VAC 50/60Hz; 1.5 kW single phase
Regulatory Compliance	CE, FCC



Headquarters:

3-4 Innovation Way
North Staffs Business Park
Stoke-On-Trent
ST6 4BF

www.tritech3d.co.uk | info@tritech3d.co.uk

STRATASYS.COM
ISO 9001:2008 Certified