



Stratasys J700 Dental

Introducing the first mass production 3D printing solution engineered specifically for clear aligner production. The Stratasys J700 Dental™ enables you to align production with demand in this growing market, whether you are scaling up an existing clear aligner operation or looking to supercharge your lab revenue by turning it into a clear aligner factory. With set-up possible in a matter of days, the J700 can quickly begin producing hundreds of arches daily, with industry-leading model quality, accuracy and repeatability.

Double-digit growth is projected in the global clear aligner market through 2021. Stratasys, a global leader in applied additive technology solutions, offers the J700 Dental as a manufacturing ready, turnkey solution for your lab, enabling you to capitalize on this growth market. High quality models with excellent surface finish quality provide the clearest path to reduced delivery times and increased patient satisfaction, all with lower dental lab costs.

With an investment of as little as one-third of competitors' pricing for similar systems, you can rely on the J700 for a fully-integrated hardware, software and materials solution with system qualification in a matter of days. Dental and orthodontic labs now have the capability to produce clear aligner arches with all the speed, reliability and ease-of-use of large-scale manufacturing facilities. Scale quickly without extensive customization or engineering. With straightforward set-up, plug-and-play connectivity and high productivity, you can deliver the highest patient satisfaction, lowest cost and quickest delivery times.

LEARN MORE AT [STRATASYS.COM](https://www.stratasys.com)





Stratasys J700 Dental

PRODUCT SPECIFICATIONS

Layer Thickness

55 microns

Material Options

VeroDent (MED670)

Applications

Clear aligner arches

Build Area

490 x 390 mm (19.3 x 15.35 in)

Workstation Compatibility

Windows 7, 8.1 and 10 (64 bit only)

Network Connectivity

LAN-TCP/IP

System Size and Weight

1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in)
430 kg (948 lbs.); material cabinet: 670 x 1,170 x 640 mm (26.4 x 46.1 x 25.2 in); 152 kg (335 lbs.)

Operating Conditions

Temperature 18-25o C (64-77o F); relative humidity 30-70% (non-condensing)

Power Requirements

100-120 VAC, 50-60 Hz, 13.5 A, 1 phase 220-240 VAC, 50-60 Hz, 7 A, 1 phase

Regulatory Compliance

CE, FCC, EAC

Software

GrabCAD Print compatibility

Designed for Clear Aligners Production

- High throughput system at a fraction of the cost of big box SLA
- Optimized for out-of-the-box clear aligner implementation
- Balances speed, quality, accuracy and repeatability with a competitive cost-per-arch
- Designed for 24/7 use with high reliability and up time
- PolyJet™ technology delivers industry leading model quality
- No handling of hazardous uncured models by operators
- No risk of model distortion through secondary processing steps
- Material resides in closed cartridges to reduce risk of contamination
- Use of cartridges enables supply chain traceability

Plug and Play Technology for Ease of Use

- Simple set-up – no configuration needed for clear aligner application
- Cost-effective alternative to customization required for stereolithography (SLA) systems
- High-volume production is possible in days, not weeks
- Designed for 24/7 use, with a throughput on par with big box SLA technology
- No special operator training required to achieve industry leading results

Centralized Production Management

- GrabCAD Print™ production management software simplifies your 3D printing workflow to facilitate fast qualification and integration into manufacturing
- Optimization of scheduling print jobs
- Printers managed from one centralized console
- Automatic material management and monitoring



TRI-TECH 3D
STANFORD MARSH GROUP

Get in touch.

HEADQUARTERS

3-4 Innovation Way, North
Staffs Business Park,
Stoke-On-Trent
ST6 4BF

info@tritech3d.co.uk
01782 814551