

Elastico™

PolyJet Rubberlike Material

Elastico™ is a superior rubberlike [PolyJet™](#) photopolymer family ideal for advanced design verification and [rapid prototyping](#). Get more durable, tear-resistant prototypes that can stand up to repeated flexing and bending. With a Shore A value of 45 in clear and black, Elastico accurately simulates the look, feel and function of rubber-like products. 3D print rubber surrounds, overmolds, soft-touch coatings, living hinges, jigs and fixtures, wearables, grips and seals with improved surface texture.

Mechanical Properties	Test Method	Value
		Black/Clear
Tensile Strength	ASTM D-412	3 - 5 MPa (435 - 725 psi)
Elongation at Break	ASTM D-412	360 - 400%
Compressive set	ASTM D-395	0.8 - 1.7 %
Tensile Tear Resistance	ASTM D-624	5 - 7.5 Kg/cm (28 - 42 lb/in)
Shore Hardness	ASTM D-2240	45 - 50 Scale A
Polymerized Density	ASTM D-792	1.1 - 1.3 (g/cm ³)

System Availability	Layer Thickness Capability	Support Structure	Available Color
J55™ Prime	High Speed mode: 18 microns (0.0001 in.)	SUP710™ (WaterJet removable)	<input checked="" type="checkbox"/> Black <input type="checkbox"/> Clear
J35™ Pro	High Speed mode: 18 microns (0.0001 in.)	SUP710™ (WaterJet removable)	<input checked="" type="checkbox"/> Black <input type="checkbox"/> Clear



Get in touch.

HEADQUARTERS
 3-4 Innovation Way, North
 Staffs Business Park,
 Stoke-On-Trent
 ST6 4BF

info@tritech3d.co.uk
 01782 814551

